

PROFESSOR-110

Construction: woodcore sandwich
TITANAL SIDEWALL construction
with U.H.M.W. running base
167, 172 cm



PROFESSOR-106

Construction: woodcore sandwich
TITANAL TCC construction
with U.H.M.W. running base
156, 163, 170 cm



PS-3

Construction: super RIM core
 ABS SIDEWALL construction
 148, 158, 168 cm



(Black)



(White)

PS-5

Construction: super RIM core
 CAP construction
 144, 152, 160, 168 cm

SWALLOW

SKIS

Model Name (Mold)	Size	Length	Effective Edge	Running Length	Tip Width	Waist Width	Tail Width	Sidecut Radius	Binding	Binding Din
PROFESSOR110 (SC-10)	167	1670	1520	1450	110	63	98	14.0	—	—
	172	1720	1570	1500	110	63	98	15.0		
PROFESSOR106 (SC-12)	156	1560	1410	1340	106	65	95	14.1	—	—
	163	1630	1480	1410	106	65	95	15.5		
	170	1700	1550	1480	106	65	95	17.0		
PS-3(PS-3)	148	1480	1390	1260	120	70	110	10.5	JLZ9-B80	2.5-9
	158	1580	1490	1360	120	70	110	12.1		
PS-5 (PS-5)	168	1680	1590	1460	120	70	110	13.9	NL29	2.5-9
	144	1440	1300	1230	115	71	100	11.1		
	152	1520	1380	1310	115	71	100	12.5		
	160	1600	1460	1390	115	71	100	14.1		
SC-9 (SC-9)	168	1680	1540	1470	115	71	100	15.8	JLZ9-B80	2.5-9
	140	1400	1310	1205	110	70	96	13.8		
	150	1500	1410	1305	110	70	96	15.2		
PS-4 (PS-4)	160	1600	1510	1405	110	70	96	17.5	JLZ9-B80	2.5-9
	170	1700	1610	1505	110	70	96	19.9		
	150	1500	1370	1220	110	74	98	15.5		
PS-103(PST-AD)	160	1600	1470	1320	110	74	98	18.0	JLZ9-B80	2.5-9
	170	1700	1570	1420	110	74	98	20.5		
	130	1300	1154	1050	103	68	90	11.5		
PST (PS-T)	110	1100	954	850	103	68	90	7.8	TZ5	0.5-4.5
	120	1200	1054	950	103	68	90	9.6		
	130	1300	1154	1050	103	68	90	11.5		
	140	1400	1254	1150	103	68	90	11.7		
GPX-200S (PSN)	80	800	667	600	100	68	90	3.9	TZ5	0.5-4.5
	90	900	767	700	100	68	90	5.4		
	100	1000	867	800	103	68	90	6.6		
	110	1100	967	900	103	68	90	7.9		
	120	1200	1067	1000	103	68	90	9.7		
	130	1300	1167	1100	103	68	90	11.7		
EX-99(BP-99SW)	140	1400	1267	1200	103	68	90	14.0	JLZ9-B100	2.5-9
99	1000	854	740	113	90	103	9.7	JLZ9-B100	2.5-9	