

SWALLOW

PS-5

Construction: super RIM core CAP construction

144, 152, 160, 168 cm



Sidecut (mm)	115 - 71 - 100			
Size (cm)	144	152	160	168
Effective Edge (mm)	1300	1380	1460	1540
Running Length (mm)	1230	1310	1390	1470
Radius (m)	11.1	12.5	14.1	15.8

with Binding NL10
Din/ISO 3-10



PS-4

Construction: super RIM core twin-tip CAP construction

150, 160, 170 cm



Sidecut (mm)	110 - 74 - 98		
Size (cm)	150	160	170
Effective Edge (mm)	1370	1470	1570
Running Length (mm)	1220	1320	1420
Radius (m)	15.5	18.0	20.5

with Binding NL10 SC
Din/ISO 3-10



PS-103

Construction: super RIM core twin-tip CAP construction

120, 130 cm



Sidecut (mm)	103 - 68 - 90	
Size (cm)	120	130
Effective Edge (mm)	1054	1154
Running Length (mm)	950	1050
Radius (m)	9.6	11.5

with Binding NL10 SC
Din/ISO 3-10



SKIBOARD

EX-99

Construction: super RIM core CAP construction

99 cm



Sidecut (mm)	113 - 90 - 103	
Size (cm)	99	
Effective Edge (mm)	854	
Running Length (mm)	740	
Radius (m)	9.7	

with Binding NL10 SC
Din/ISO 3-10



JUNIOR

PST

Construction: super RIM core twin-tip CAP construction
110, 120, 130, 140 cm (Jr. model)



Sidecut (mm)	103 - 68 - 90			
Size (cm)	110	120	130	140
Effective Edge (mm)	954	1054	1154	1254
Running Length (mm)	850	950	1050	1150
Radius (m)	7.8	9.6	11.5	11.7

with Binding NT5
Din/ISO 0.5-4.5



SG-300

Construction: super RIM core CAP construction
90, 100, 110, 120, 130, 140 cm (Jr. model)



Sidecut (mm)	100 - 68 - 90 (90cm)		103 - 68 - 90 (100 -140cm)			
Size (cm)	90	100	110	120	130	140
Effective Edge (mm)	767	867	967	1067	1167	1267
Running Length (mm)	700	800	900	1000	1100	1200
Radius (m)	5.3	6.4	7.9	9.7	11.7	14.0

with Binding NT5
Din/ISO 0.5-4.5



S-GIRLS

Construction: super RIM core CAP construction
90, 100, 110, 120, 130, 140 cm (Jr. model)



Sidecut (mm)	100 - 68 - 90 (90cm)		103 - 68 - 90 (100 -140cm)			
Size (cm)	90	100	110	120	130	140
Effective Edge (mm)	767	867	967	1067	1167	1267
Running Length (mm)	700	800	900	1000	1100	1200
Radius (m)	5.3	6.4	7.9	9.7	11.7	14.0

with Binding NT5
Din/ISO 0.5-4.5



RENTAL USE

ROTACION

Construction: super RIM core CAP construction
140,150,160, 170 cm



Sidecut (mm)	111 - 67 - 98			
Size (cm)	140	150	160	170
Effective Edge (mm)	1267	1367	1467	1567
Running Length (mm)	1190	1290	1390	1490
Radius (m)	10.0	12.0	13.5	16.0

ROTACION Jr.

Construction: super RIM core CAP construction
80, 90, 100, 110, 120, 130, 140 cm (Jr. model)



Sidecut (mm)	100 - 68 - 90 (80-90cm)		103 - 68 - 90 (100 -140cm)				
Size (cm)	80	90	100	110	120	130	140
Effective Edge (mm)	667	767	867	967	1067	1167	1267
Running Length (mm)	600	700	800	900	1000	1100	1200
Radius (m)	3.9	5.3	6.4	7.9	9.7	11.7	14.0