WooTest

Ingredients:

- *Durable and fast 4001 sintered running base
- *Ultra-high-molecular-weight polyethylene orbicular sidewalls....Extra resistant to abuse.
- *Strategically blended Basswood & Ash vertical laminate wood core; with "Book ended" precision.
- *Oversized 2.2m edges with full wrap tip and tail; extra protection from impacts.
- *Rubberized epoxy; flexible and impact resistant with ultra high adhesion properties.
- *Lightweight 19 oz. triaxial fiberglass.
- *Carbon fiber re-enforcements; correctly engineered for a lighter-stiffer-damper ride.
- *VDS Rubber damping around the skis entire Perimeter. Reduces vibrations and improves bond strength.
- *Perforated VDS Rubber binding zone; reduces vibration and strengthens the binding mount zone.

^{*187} version displayed with the new WooTest inset into the Protest.

Tip Splay	Early Splay	Camber Zone	Early Splay	Tail Splay

WooTest

Tip (MM)

Mid (MM)

Tail (MM)

Base Length (CM)

Tip Height (CM)

Tail Height (CM)

Tip Taper (CM)

Tail Taper (CM)

Turn Radius (M)

Total Tip Splay (CM)

Total Tail Splay (CM)

Side Cut length (CM)

Camber Height (mm)

Boot Center negative (CM)

Camber contact Length (CM)

<u> 187</u>

124

116

4.5

60

54

116

196

104

109

